



- Multidirectional anti-vibration/shock mounts.
- Displacement under shock from 45 to 70mm.
- Transmissibility :  $Q < 10$ .
- Resonant frequency 6Hz for normal load.
- Temperature range :  $-30^{\circ}\text{C} +90^{\circ}\text{C}$ .
- Great adaptability / versatility.

Specials on request (materials, size and interfaces, etc.).

Dimensions are in mm. For reference only.

Series	Dimensions & Load										nom. load (daN)	axial stiffness (N.mm <sup>-1</sup> )	mass (kg)
	model	H	L	I	e	v	t	M	s	Sp			
Materials and finishes  <b>BF45</b> Elastomer: polychloroprene Top and bottom interfaces: salt fog anti corrosion paint  Other materials on request	-30	100	150	114	10	27	9	M10	5	-	30	25	1,2 (2,3) (3,5)
	-45										45	35	
	-60										60	50	
	-85										85	65	
	-110										110	85	
	-130										130	100	
	-170	126	165	140	13	41	13	M20	10	-	170	130	3,4 (3,8) (4,7)
	-230										230	175	
	-320										320	230	
	-425										425	230	
-500	154	250	210	14	41	18	M24	15	-	500	400	12,5	
-625										625	500		
-800										800	650		
-1080										1080	840		

Example BF45-230e15

<b>B</b>	<b>F</b>	<b>4</b>	<b>5</b>	<b>-</b>	<b>2</b>	<b>3</b>	<b>0</b>	<b>e</b>	<b>1</b>	<b>5</b>
----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------

Prefix: 'low frequency' mount from the BF45 series

Model: -230 height: 126mm width: 165mm interface: M20

nom. load: 230 daN axial average stiffness: 175 N.mm<sup>-1</sup>

Spacer: e15 thickness: 15mm

