



- Multidirectional anti-vibration/shock mounts.
- Structure-borne noise isolation.
- Displacement under shock up to 60mm along vertical direction and 40mm along radial.
- Transmissibility : $2 < Q < 6$.
- Transmitted acceleration limited to 5g along longitudinal direction and to 15g along vertical and transversal.
- Temperature range : $-20^{\circ}\text{C} + 40^{\circ}\text{C}$.

Dimensions are in mm. For reference only.

Series
Materials and finishes (meets RoHS requirements)
LSY
Leaf and washer: stainless steel
Compound: epoxy resin
Bush: nylon and elastomer
Coating : Neoprene Paint

type	static load (kg)			A	B	C	D	E	F	G	H	I	J	mass (kg)
	min	nom	max											
-10	9	10	18	203	51	134	48	36	M6	41	32	M8	22	0,68
-20	18	20	35	203	51	134	48	36	M6	42	32	M8	23	0,80
-45	35	45	55	216	51	166	48	36	M10	56	32	M12	24	1,02
-70	55	70	90	216	51	166	48	36	M10	57	32	M12	25	1,13
-110	90	110	135	297	51	166	48	36	M10	58	32	M12	26	1,25
-180	135	180	250	297	102	229	96	72	M16	77	64	M20	39	5,90
-320	250	320	380	297	102	229	96	72	M16	79	64	M20	41	6,57
-450	380	450	550	297	102	229	96	72	M16	81	64	M20	43	7,25



Example
LSY-45



Prefix:
'leaf spring'
mount
from the
LSY series

Model: -45
nominal static load: 45kg
height: 166mm
length: 216mm
width: 51mm
mass: 1,02kg

